

# CPA-1001-720H

## 20 dB SMT COUPLER

RoHS Compliant and Pb-Free Product  
Package: S06

### Features

- Frequency Range: 5 MHz to 1000MHz
- Industry Standard SMT package
- Nominal Coupling 20 dB
- Available in Tape-and -Reel
- Low Cost and RoHS Compliant
- 75Ω Characteristic Impedance

### Product Description

The CPA-1001-720H coupler is designed for applications that require small, low cost, and highly reliable surface mount components. Applications may be found in broadband, wire-less and other communications systems. These units are built Lead-Free and RoHS compliant. S-Parameters are available on request.







### Specifications

Parameter	Specification			Unit
	Min.	Typ.	Max.	
Frequency Range	5		1000	MHz
Nominal Coupling	21	20.5	20	dB
Coupling Flatness	-0.7		+0.7	dB
Mainline Loss		0.4	0.75	dB
Directivity	12	20		dB
Return Loss	17	25		dB

Note: Typical values represent midband performance at T=25 °C.

### Schematic






### Pin Out

Pin	Name
1	Input
2	Ground
3	Coupled
4	Terminated
5	Ground
6	Output

### Absolute Maximum Ratings

Parameter	Rating	Unit
RF Power	+33	dBm
Operating Temperature	-55 to +100	°C
Storage Temperature	-55 to +100	°C

### Package Drawing - S06



Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability. Specified typical performance or functional operation of the device under Absolute Maximum Rating conditions is not implied.

RoHS status based on EUDirective2002/95/EC (at time of this document revision).

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by MiniRF, Inc. ("MiniRF") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of MiniRF. MiniRF reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.